
























Sr No	Product Description	Product Image	Properties	General Application Area
1	WD 40[32G]		1) Water Displacement	<p><u>STOPS SQUEAKS, DRIVES OUT MOISTURE, CLEANS AND PROTECTS, LOOSENS RUSTED PARTS, FREES STICKY MECHANISMS</u></p> <ul style="list-style-type: none"> ➤ Battery terminal ➤ Spark Plug, PCB's, Circuits, Etc.
2	WD 40[63.8G]		2) Penetration	
3	WD 40[170G]		3) Protection	
4	WD 40 [420 ML] (Industrial Pack with 360° Spray)		4) Lubrication	
5	WD-40 with SMART STRAW [500 ML]		5) Cleaning	
5	WD 40 [5 LTR]			
6	WD 40[200 LTR]			





7	FEVIKWIK 203 [20 GM]		<ol style="list-style-type: none"> 1) Fast Drying 2) Solvent Less 3) Fast Setting 4) Low Viscosity 5) Good Penetration 	<p><u>CYANOACRYLATE ADHESIVE</u></p> <ul style="list-style-type: none"> ➤ Making of O Ring ➤ Bonding Metal, Plastics and Rubber Components ➤ Sign Plates ➤ Name Plates ➤ Reflectors ➤ PVC sheet bonding in door manufacturing
8	FEVIKWIK GP [20 GM]			
9	FEVIKWIK GEL [20 GM]		<ol style="list-style-type: none"> 1) Non-Dripping 2) Controlled Flow 3) No Spillage 	<p><u>GEL</u></p> <ul style="list-style-type: none"> ➤ PVC sheet bonding in door manufacturing ➤ Joining connector to hose pipe ➤ Fixing Rubber Gasket to metal part of electrical panel
10	FEVITITE SUPER STRONG EPX RESIN [1KG] (Part 1)		<ol style="list-style-type: none"> 1) Two component Adhesive 2) Sets in 4 Hours 3) Excellent Bond Strength 4) Bonds almost all types of material 5) Excellent Chemical Resistance and long-lasting bonds 	<p><u>TWO COMPONENT SUPER STRONG EPOXY ADHESIVE THAT BONDS VIRTUALLY ANYTHING</u></p> <ul style="list-style-type: none"> ➤ Bonding of Glass, Metal, Wood, FRP, Etc. ➤ Crack filling in Metal ➤ Bonding of metal tools/ metal components ➤ Toys Mfg. ➤ Construction
11	FEVITITE SUPER STRONG HRDN [800 GM] (Part 2)			
12	FEVITITE SUPER STRONG EPX ADH [180 G] (Combi pack)			
13	FEVITITE RAPID AND CLEAR [7 GM 20 EA]		<ol style="list-style-type: none"> 1) Two component Adhesive 2) Sets in 5 minutes 3) Bonds almost all types of material 4) Excellent Chemical Resistance and long-lasting bonds 	<ul style="list-style-type: none"> ➤ Bonding of Glass, Metal, Wood, painted Metal, FRP, Etc. ➤ Crack filling in Metal ➤ Bonding of metal tools/ metal components ➤ Toys Mfg. ➤ Construction ➤ Imitation Jewellery
14	FEVITITE RAPID AND CLEAR [13 G]			





15	FEVITITE RAPID AND CLEAR [36 G]		<p>5) Two component Adhesive</p> <p>6) Sets in 5 minutes</p> <p>7) Bonds almost all types of material</p> <p>8) Excellent Chemical Resistance and long-lasting bonds</p>	<ul style="list-style-type: none"> ➤ Bonding of Glass, Metal, Wood, painted Metal, FRP, Etc. ➤ Crack filling in Metal ➤ Bonding of metal tools/ metal components ➤ Toys Mfg. ➤ Construction ➤ Imitation Jewellery
16	FEVITITE RAPID AND CLEAR [90 GM]			
17	M-SEAL REGULAR [250 GM]		<p>1) Two Component Epoxy Putty</p> <p>2) Sets in 90 Minutes</p> <p>3) Excellent chemical resistance</p> <p>4) Excellent insulation resistance</p> <p>5) Can be machined to desire shape</p>	<p><u>MULTI-PURPOSE SEALANT FOR SEALING, JOINING, FIXING, REPAIRING ETC.</u></p> <ul style="list-style-type: none"> ➤ Gap Filling ➤ Pipe Leakages ➤ Insulations of Electrical Junction Boxes, meters etc. ➤ Sealing holes ➤ Leakages on roofs ➤ Motor Balancing ➤ Foundry ➤ Offline Leakages
18	M-SEAL REGULAR [1 KG]			
19	M-SEAL REGULAR [4 KG]			
20	M-SEAL REGULAR WHITE [500 GM]			
21	M-SEAL PHATAPHAT [250 GM]			<p>1) Two Component Epoxy Putty</p> <p>2) Sets in 30 Minutes</p> <p>3) Excellent chemical resistance</p> <p>4) Excellent insulation resistance</p> <p>5) Can be machined to desire shape</p>
22	M-SEAL PHATAPHAT [1 KG]			




23	Feviseal ACETOXY CURE [280 ML]		<ol style="list-style-type: none"> 1) Single Component 2) Excellent Adhesion to Glass & Metals 3) Non-Corrosive 4) No Mixing Required 5) Temperature Resistant 6) Free from bad smell 7) Non-Sag 	<p><u>ONE COMPONENT ACETIC SILICONE SEALANT FOR SEALING & JOINING APPLICATIONS</u></p> <ul style="list-style-type: none"> ➤ Gap Filling ➤ Bonding mirror hanging fixtures ➤ Gap filling on Roof, stretch panels, Etc. in Auto OEM/Bus Body ➤ Sealing window glass, Aluminum frames, Etc. ➤ Seal cracks around window/glass/pipes/Metal ➤ Filling void space 	
25	RUSTOLENE (5LT)		<ol style="list-style-type: none"> 1) Safe and easy to handle 2) Non-corrosive - No damage to tools and metal pipe fittings 3) Low viscosity - High coverage and offer good penetration 4) Good surface wetting - Uniform film spreading property 	<p><u>RUST DISINTEGRATOR</u></p> <p><u>Cleaning Method -</u></p> <ul style="list-style-type: none"> ➤ Immersion of rusted part ➤ Brush application on rusted part 	
26	RUSTOLENE (500ML)			<p>❖ <u>Cleaning of various components like</u></p> <ul style="list-style-type: none"> ➤ Bearing ➤ Gearbox ➤ Generator ➤ Jammed nuts–bolts 	<p>❖ <u>Maintenance and Cleaning of –</u></p> <ul style="list-style-type: none"> ➤ Pumps ➤ Heat exchangers ➤ Boilers ➤ Cooling Towers
27	RUSTOLENE (1LT)				<p>Farm equipment's</p>

28	WD-40 CONTACT CLEANER (400 ML)		<ol style="list-style-type: none"> 1) NSF K2 CERTIFIED (PREMIUM CERTIFICATION) – CAN BE USED IN FOOD AND PHARMA INDUSTRIES 2) HIGHEST Kb SCORE – ABOVE AVERAGE CLEANING PROPERTIES 3) DIELECTRIC STRENGTH IS 33 KV MAKING IT SAFE TO USE ON ELECTRIC PARTS 4) 100% evaporating and offline type 5) Excellent and fast cleaning 6) Quick Drying 7) Plastic Safe 8) No CFC with CO2 propellant 9) Non-Residual 	<p><u>USED FOR CLEANING OF ELECTRICAL EQUIPMENT'S SUCH AS:</u></p> <ul style="list-style-type: none"> ➤ PCBs ➤ Potentiometers ➤ Coils ➤ Connectors ➤ Panel boards ➤ Relays ➤ Rheostats ➤ Junctions boxes ➤ Control switches ➤ Telephone CT Boxes ➤ Fuses ➤ Motor windings ➤ Circuit breakers ➤ Sensors ➤ Alarm and signal systems ➤ Cleaning of moulds ➤ Cleaning of tools
29	STEELGRIP- 1.8CMX6.5MX0.125MM [6.5M] BLACK		<ol style="list-style-type: none"> 1) PVC Insulation tapes 2) Conforms to IS:7809 (Part 3, Sec 1) 3) Self Extinguishing 4) Protects from electrolytic corrosion 5) Excellent Water resistance 6) Suitable for primary insulation up to 440 V (Colours Available: Red, Green, Blue, Black, White and Yellow) 	<p><u>SELF EXTINGUISHING ELECTRICAL INSULATION TAPE</u></p> <ul style="list-style-type: none"> ➤ Wire Insulation ➤ Electric Motors ➤ Resistors ➤ Capacitors ➤ Electric Circuits ➤ Transformers ➤ Chrome Plating
30	STEELGRIP- 1.8CMX6.5MX0.125MM [6.5M] BLUE			
31	STEELGRIP- 1.8CMX6.5MX0.125MM[6.5 M] GREEN			
32	STEELGRIP- 1.8CMX6.5MX0.125MM [6.5M] RED			
33	STEELGRIP- 1.8CMX6.5MX0.125MM[6.5 M] WHITE			
34	STEELGRIP- 1.8CMX6.5MX0.125MM[6.5 M] YELLOW			

35	HOLDTITE TEFLON TAPE 80 MICRON		<ol style="list-style-type: none"> 1) Resistant to most of the chemicals 2) Withstands high pressure 3) Uniformly thick (80 micron) 4) High elongation width wise 	<p><u>USED FOR JOINING AND SEALING OF THREADED INDUSTRIAL PIPELINES OF:</u></p> <ul style="list-style-type: none"> ➤ Hot water ➤ Cold water ➤ Steam ➤ Gases ➤ Acid Alkali ➤ Solvents
36	HOLDTITE PLUS PTFE TAPE 100 MICRON			
37	HOLDTITE LIQUID SEALANT BLACK [100GM]		<ol style="list-style-type: none"> 1) Shellac based compound 2) Good resistance to corrosion 3) Conforms to IS:3477 4) Non - Hazardous 	<p><u>SINGLE COMPONENT SEALANT USED FOR JOINING</u></p> <ul style="list-style-type: none"> ➤ Pipe and Sockets joints ➤ Hot and Cold-water Industrial Pipes ➤ Gasket Dressing ➤ Leakage in Flange joints ➤ Protection of foundation nuts and bolts against rusting and jamming
38	HOLDTITE LIQUID SEALANT BLACK [200GM]			
39	HOLDTITE LIQUID SEALANT BLACK [500GM]			
40	HOLDTITE LIQUID SEALANT BLACK [1KG]			
41	FLEX KWIK [20 GM]		<ol style="list-style-type: none"> 1) Good Adhesive Properties 2) Specially Made for Flex Bonding 	<p><u>INSTANT ADHESIVE FOR FLEX & PVC DOORS</u></p> <ul style="list-style-type: none"> ➤ Used for Rough Plumbing ➤ Used for bonding of: <ol style="list-style-type: none"> 1. Plastic 2. Metal 3. Rubber 4. Wood 5. Leather 6. Ceramic
42	MASKING TAPE [24 MM X 20 MM] (Self Adhesive Paper Tape)		<ol style="list-style-type: none"> 1) Self-Adhesive Paper Tape 2) Easy to tear 3) Leaves no residue 4) Does not leave bond even in higher temperatures 5) Thickness of Shrink Sleeve- Above 50 Microns 	<p><u>SELF ADHESIVE PAPER TAPE</u></p> <ul style="list-style-type: none"> ➤ Use in furniture industry ➤ Used in painting and polishing ➤ Used in labelling applications ➤ Applications in auto and paint industry

43	FLOOR MARKING TAPE [48 M X 20 M]		<ol style="list-style-type: none"> 1) Long Lasting Adhesion 2) Easy to Apply and Remove 3) High Visibility 4) Waterproof 5) No drying time. Work can continue during application 	<p><u>FLOOR MARKING TAPE</u></p> <ul style="list-style-type: none"> ➤ Applicable for marking lanes for organized movement in public places or warehouses. ➤ Perfect for floor lining. Excellent for infrastructural projects. ➤ Suitable for multiple substrates
44	MOTOMAX CHAIN LUBE [100 ML]		<ol style="list-style-type: none"> 1) Protects and Prevents Chain breakage 	<p><u>LONG LASTING LUBRICANT SPRAY</u></p> <p><u>An unique lubricant that coats, preserves and protects the chain and sprocket of Bikes, Motorbikes, Sports Bikes, Cruiser Bikes, Bullets, Bicycles</u></p>
45	MOTOMAX CHAIN LUBE [100 ML]		<ol style="list-style-type: none"> 2) It coats, protects and preserve 3) Easy to use aerosol can 4) Long Lasting Lubricant 5) Deep Penetration into the tightest areas to provide maximum lubrication 	<ul style="list-style-type: none"> ➤ Contains solvents to penetrate grime and adhere to the metal parts of any industry ➤ Equally effective on both non-O ring and O ring type chains ➤ Water and salt-resistant – protects against corrosion
46	FEVI-BOND [25 ML]		<ol style="list-style-type: none"> 1) Instant Sticking & Strong Bonding 	<p><u>SYNTHETIC RUBBER BASED ADHESIVE</u></p>
47	FEVI-BOND [50 ML]		<ol style="list-style-type: none"> 2) Easy to apply 	<ul style="list-style-type: none"> ➤ Can be used to fill cracks in power transmission V Belt ➤ Ideal for sticking leather rubber rexine canvas cork
48	FEVI-BOND [90 ML]		<ol style="list-style-type: none"> 3) Can be used on multiple surfaces with varied substrates as embellishments 	<ul style="list-style-type: none"> ➤ It has a strong bond that helps stick a variety of materials.
49	D-KLOG		<ol style="list-style-type: none"> 1) Clear Blockages in 30 Minutes 2) Removes Clogs 3) Kills Bad Smell & Odour 4) Kills Germs & Bacteria 	<p><u>REMOVES CLOGS, BLOCKAGES, IN WASHBASIN, SEPTIC TANK, SINKS</u></p> <ul style="list-style-type: none"> ➤ Finds applications in Fan Industry & other industries for cleaning purpose ➤ Removal of blockages in industrial pipelines ➤ Protects the industrial tanks and pipes from manual damage

50	LEAKGUARD PVC SOLVENT CEMENT [1 L]			<p><u>FOR PVC PIPE FITTINGS</u></p> <p>It is used in joining underground electric pipes</p>
51	LEAKGUARD PVC SOLVENT CEMENT [500 ML]			<ul style="list-style-type: none"> ➤ It is used in broom manufacturing industry
52	LEAKGUARD PVC SOLVENT CEMENT [200 ML]		<ol style="list-style-type: none"> 1) Forms a water-proof seal 2) Longer shelf life 3) High hold strength 4) Precise Composition 	<ul style="list-style-type: none"> ➤ Cold Water Pipeline & PVC Pipes & Fittings ➤ Agriculture Pipeline, Boring Application & Door Manufacturing
53	LEAKGUARD CPVC SOLVENT CEMENT		<ol style="list-style-type: none"> 1) Complies to ASTM F-493 2) Heat Resistant upto 90 degree C 3) Strong & Leak Proof 4) Fast Drying 5) Moisture Resistant 	<p><u>FOR CPVC PIPE FITTINGS</u></p> <ul style="list-style-type: none"> ➤ Finds application in Hot & Cold-Water Pipelines in Industry ➤ CPVC Pipes & Fittings
54	M-SEAL RTV (CLEAR) [85 GM]		<ol style="list-style-type: none"> 1) Withstands extreme temperature ranging from -40deg C to + 220deg C 2) Good Oil Resistant 	<p><u>GASKET MAKER</u></p> <ul style="list-style-type: none"> ➤ Used in light and heavy automotive industries for gasket making
55	M-SEAL RTV (RED) [85 GM]		<ol style="list-style-type: none"> 3) Can be used for pre-cut paper, sheet or rubber gaskets 4) High Pressure Resistant 	<ul style="list-style-type: none"> ➤ Flange sealing applications ➤ RTV Silicone Rubber can be used to cast materials including Wax, Gypsum, Low Melt Alloys/Metals
56	M-SEAL RTV (GREY) [85 GM]			<ul style="list-style-type: none"> ➤ Industrial Applications Include Aviation, Aerospace, Consumer Electronics, and Microelectronics.

57	ROFF CERA CLEAN [1 L]		<ol style="list-style-type: none"> 1) High quality rapid action cleaner & degreasing solution 2) Removes stains 3) Retains tile gloss 4) For use on mosaic, ceramic, vitrified tiles, bathtubs, wash basin 	<p><u>TILE FLOOR CLEANER LIQUID</u></p> <ul style="list-style-type: none"> ➤ Cleaning of Industrial Shop Floor ➤ Cleaning of commercial floor and wall tiles
58	BRITO – BRASS POLISH		<ol style="list-style-type: none"> 1) It safely cleans, polishes and protects items of brass, copper, silver and stainless steel and provides instant and long-lasting glow 2) It effectively removes tarnish, rust, water stains and oxidation without scratching the surface 	<p><u>POLISH FOR ALL METAL SURFACES</u></p> <ul style="list-style-type: none"> ➤ It has applications in industries for removal of oxidations in metallic equipment's ➤ Can be used by specialist restaurants serving gourmet food to keep their cutlery bright and shining ➤ Used for protection of metallic equipment's in industries
59	Feviseal NEUTRAL CURE [280 ML]		<ol style="list-style-type: none"> 1) Fills upto 17 mm of gap filling 2) Isocyanide free 3) Flexible bonding with long term durability 4) Can be used for all types of general sealing 5) No smell does not sag 6) Anti-Fungal & Anti Algal 	<p><u>NEUTRAL CURE SILICONE SEALANT</u></p> <ul style="list-style-type: none"> ➤ Used in general sealing applications in pharma and food industry ➤ Used in interior building applications like sealing windows & doors ➤ Frame and floor filling